

COMBINED CUTTER-BENDER

VERSATILE AND MULTIPURPOSE MACHINE

The combined cutter-bender version has the same characteristics as our range of on sitework benders and, as a cropper, it cuts pedal-operated stroke by stroke, being possible to stop the blade instantly at any time during the cut.

- 8 cutting edges blades.
- Cut protector for safety.
- The entire manufacturing process of the rebar machines is carried out in our facilities, which allows us to maximize the useful life and quality of the product.



COMBI 32/36

TECHNICAL FEATURES

Round Steel		COMBI 26/32						COMBI 32/36					
		Cut			Bender			Cut			Bender		
		Number of bars											
		1	2	3	1	2	3	1	2	3	1	2	3
Smooth	Rebar diameter	25-#8	18-#5	14-#4	32-#10	25-#8	22-#7	32-#10*	20-#6	16-#5	36-#11	28-#8	24-#7
B400S - Grade 40		22-#7	16-#5	12-#3	28-#8	22-#7	18-#5	28-#8*	20-#6*	16-#5*	32-#10	25-#8	22-#7
B500S - Grade 60		20-#6	14-#4	10-#3	25-#8	20-#6	18-#5	25-#8	18-#5	14-#4	28-#8	22-#7	20-#6
Turntable speed	r.p.m.	7.8						7.8					
Engine power	kW	2.2 / 2.6						3 / 3.6					
Dimensions and Net weight	kg	300						305					
	mm	950 x 730 x 933						950 x 730 x 933					

* The table for gross diameters will be needed for cutting some of these diameters (not supplied with the machine).