

STIRRUP BENDERS

MACHINES WITH OPTIONAL PROGRAMMER

Our electric stirrups are specially designed for any kind of stirrups, producing a large number of stirrups per hour. It is a simple and safe range to operate that has a pedal control and an emergency stop button.

- Large production : 700 to 1.000 stirrups/hour (DAE16L)
- 350 to 500 stirrups/hour (D24L)
- Elevated turn table (DAE16L).
- Feeding of material from the left side and turning of stirrup towards the operator.
- Bolt bending. Possibility of bending different radius.
- Control electric equipment at low voltage (48 V).
- 2 rod guides and 2 measure limits.
- Bending angles selection with pin: D42L (0-257°), DAE16L (0-250°).



DAE16L



D24LP

TECHNICAL FEATURES

Round Steel		DAE16L						D24L - D24LP					
		Bar diameter											
		ø6 - #2	ø8 - #2	ø10 - #3	ø12 - #3	ø14 - #4	ø16 - #5	ø6 - #2	ø10 - #3	ø14 - #4	ø16 - #5	ø20 - #6	ø24 - #7
Smooth	Number of bars	10	8	4	2	1	1	10	6	4	4	2	1
B400S - Grade 40		9	5	3	1	1	-	10	6	4	4	1	-
B500S - Grade 60		9	4	2	1	-	-	10	6	4	3	1	-
Turntable speed	r.p.m.	28						11					
Engine power	kW	0.66 / 1.1						1.1					
Dimensions and Net weight	kg	110						187					
	mm	595 x 490 x 893						800 x 590 x 900					