

ASPHALT & CONCRETE CUTTERS

ASPHALT & CONCRETE CUTTERS

The user regulates the depth of the disc by means of a comfortable handwheel, allowing a continuous and easy control of the work.

They are equipped with 3 commercial belts that may be tightened with the screws in the frame, which means quick and easy maintenance. The cooling system takes a universal connector so it can be connected directly to a water hose.

- Specially designed to be transported in all types of cargo vehicles.
- Quick hose connector.
- Diamond blade of 400 or 500 mm diameter.
- Maximum depth of cut: 190 mm.
- Height adjustable handlebar.
- Robust cutting guide that marks the position of the blade at all the time.
- Holding brake attached to the frame (optional element for the CJP model).



CJP
Plastic deposit



CJM
Metal deposit

TECHNICAL FEATURES

		CJP 400	CJP 500	CJM 500
Water deposit net capacity	l	25		54
Motor power	CV/kW	13/9,6		13/9,6
Max. diameter of cutting blade	mm	400 mm	500 mm	500 mm
Max. cutting depth with 400 mm blade	mm	140 mm		140 mm
Max. cutting depth with 500 mm blade	mm	--	190 mm	190 mm
Petrol deposit net capacity	l	6,5 l		6,5 l
A-weighted sound power level	LwA	112 dB (A)		112 dB (A)
KwA uncertainty	LpAeq	94 dB (A)		94 dB (A)
Weighted emitted sound pressure level at the workplace	K	2		2
KpWA uncertainty	Lpc pico	< 130 dB (A)		< 130 dB (A)
Weight	kg	97	99	117
Dimensions	mm	890 x 590 x 940		1110 x 600 x 593