

WET CUT

MASONRY SAWS TVD

OPTIMAL CUTTING ACCURACY IN LARGE PIECES

The TVD put together all the advantages of the TVR model, with larger dimensions and it is fitted with an extremely robust and height-adjustable head, which makes it suitable for accurate works, especially hard works with very long pieces.



TVD



Maximum cutting length: 1190 mm.



It can be supplied with table extension as an option.

TECHNICAL FEATURES

		TVD 90-3M	TVD 90-4	TVD 125-3M	TVD 125-4
Motor		Single phase	Three-phase	Single phase	Three-phase
kW/CV (50/60 Hz)		2,2/2,5	3/3,5	2,2/2,5	3/3,5
Voltage (2)		230 V (50 Hz)	230/400 V (50 Hz)	230 V (50 Hz)	230/400 V (50 Hz)
Thermal protector		YES	NO	YES	NO
Cutting blade diameter	mm	350 x 25,4	350 x 25,4	350 x 25,4	350 x 25,4
STRAIGHT CUT					
Cutting height (1)	mm	100		100	
Cutting length (3)	mm	870		1.190	
Cutting length (4)	mm	800		1.120	
MITER CUT (45°)					
Cutting height (1)	mm	85		85	
Cutting length (3)	mm	860		1.180	
Longitud de corte (4)	mm	780		1.100	
Machine max. dimensions	m	1,40 x 0,82 x 1,08		1,695 x 0,73 x 1,305	
Net weight	kg	80		153	
Packaging dimensions	m	1,43 x 0,55 x 0,57		1,80 x 0,9 x 0,85	
A LwA-weighted sound power level	dB (A)	100		100	
KwA uncertainty	dB (A)	2		2	
Weighted emitted sound pressure level at the workplace	dB (A)	87		87	
KpwA uncertainty	dB (A)	780		780	

[1] Single run. [2] Other voltages and frequencies to be considered. [3] Thickness 10 mm. [4] Thickness 75 mm. [5] Thickness 70 mm.

In our constant improving, we reserve the right to make modifications. The images in this catalogue are merely illustrative and in no case contractual.