

WOOD SAW TLE

DESIGNED TO CUT WOOD ON SITE

With optimum cutting precision, the TLE are very comfortable and easy to use for the operator. They have an extendable table to support the longest pieces.

- Widia cutting disc with a high resistant protector.
- Motor brake stopping in less than 10 seconds.
- Cutting slot and disc guard borders in plastic material.
- Wheels for an easier movement of the saw.



TLE

TECHNICAL FEATURES

| | | TLE 3M | TLE 4 |
|--|------------------|--------------------|-------------------|
| Motor | | Single phase | Three-phase |
| Motor power | kW/CV (50/60 Hz) | 2,2 - 2,5 | 2,9 - 3,6 |
| Voltage | | 230 V - 50 Hz | 230/400 V - 50 Hz |
| Thermal protector | | YES | NO |
| Disc in./out. diameter | mm | 30/315 | 30/315 |
| Max. cutting height | mm | 85 | |
| Machine max. dimensions | m | 0,78 x 1,37 x 0,98 | |
| Net weight | kg | 64 | |
| Packaging dimensions | m | 0,81 x 0,98 x 0,51 | |
| A LwA-weighted sound power level | dB (A) | 100 | |
| KwA uncertainty | dB (A) | 2 | |
| Weighted emitted sound pressure level at the workplace | dB (A) | 92 | |
| KpWA uncertainty | dB (A) | 2 | |